

SURFACING RANGE

QZ

Light vibrating screed

Thanks to its oscillating system, the QZ vibrating screed can work in both directions.




- Rounded edges on the profile
- Profiles from 2 to 4 metres long
- The 200mm profile is designed to provide good buoyancy
- Curved profile's shape to push and drag the concrete
- Rotating system integrated in the handle, which also enables changing angle of the screed




Profiles

Length (m)	Weight (kg)
2	9.6
2.5	12.5
3	14
4	19.2




+ Complete range

There is a wide range of models suitable for all clients and a variety of engines.




+ Oscillating profile

By turning the handle, the profile oscillates until the proper inclination is achieved, while changing the working direction.



+ Accessibility

Thanks to its design, it allows access to the edges of facades and pillars, reaching the limits of the flooring.



+ Bidirectional

The QZ oscillating screed allows you to work in both directions.

Technical Data Petrol Screens

MODEL	Engine	Power (CV)	Fuel	Fuel tank capacity (L)	Frequency (vib/min)	Centrifugal force (N)	Weight (Kg)
QZ H	HONDA GX25 4t/st	1.1	Unleaded Petrol	0.55	Up to 9,000	1,500	12.5

Technical Data Electric Screens

MODEL	Engine	Power (W)	Frequency (vib/min)	Centrifugal force (N)	Weight (Kg)
QZ E	External Vibrator 230V 1~	135	2,850	700	10.5
QZ E TURBO	Vibrator 230V 1	500	12,000	1,300	12

*Both available also in 115V version upon request.