

SURFACING RANGE

QX

Light vibrating screed

QX screeds stand out for their extraordinary lightness combined with high performance and great economy of use.



- High strength aluminium profile
- Rounded edges on the profile
- Flatness of the profile is strictly controlled
- The 200mm profile is designed to provide good buoyancy

Profiles

Length (m)	Weight (kg)
1.5	4.6
2	6.2
2.5	7.8
3	9.3
4	12.5



Technical Data Petrol Screeds

MODEL	Engine	Power (CV)	Fuel	Fuel tank capacity (L)	Frequency (vib/min)	Centrifugal force (N)	Weight (Kg)
QX H	HONDA GX25 4t/st	1.1	Unleaded Petrol	0.5	Up to 9,000	1,500	9.8

Technical Data Electric Screeds


MODEL	Engine	Power (W)	Frequency (vib/min)	Centrifugal force (N)	Weight (Kg)
QX E	External Vibrator 230V 1~	150	3,000	700	8
QX E TURBO	Vibrator 230V 1	500	12,000	1,300	12

*Both available also in 115V version upon request.




+ Economy of use

It offers a perfect value for money considering its performance.




+ Robustness

The QX vibrating screed has few parts susceptible to breaking, which makes it a very robust product.



+ Lightness and manageability

It can be handled by one person, which simplifies its transportation and use.



+ Complete range

A wide range of vibrating screeds tailored to each client's needs, with different engines.